



Residential Single/
Dual Swing Technology

Gate Openers

- Cost Efficient Operation
- Quick Installation
- Easy Transmitter Programming
- Soft Start / Soft Stop
- Solar Compatible
- Includes Battery Backup
- Works with All Types of Gates
- 2-Year Warranty
- UL 325 Compliant



4000 XLS



3000 XLS



2000 XLS

4000 XLS 3000 XLS 2000 XLS

Common Electrical Features

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Hz input, 18V AC, 40 VA. output, transformer, regulated to 14V DC through control board
- Powered by a reliable 12 Volt (120 Watt) DC motor, 16:1 planetary gear drive system
- “Sleep draw” is 15 mA; “active draw” is 3 to 7 amps
- Operator length for 3000XLS: with arm fully retracted is 40.25" (102 cm)
- The PRO-SW3200XLS works as a second gate operator when combined with a PRO-SW3000XLS. The PRO-SW3200XLS includes a 40ft power cable.
- Operator length for 4000XLS: with arm fully retracted is 46.25" (117 cm)

Common Engineering Features

- The control board can be programmed for pull-to-open or push-to-open
- Operating temp -5 F (-21C) to +160 F (71 C)
- Opening time: From 15 to 20 seconds
- Range of arm stroke: is up to 15"(33 cm) with 2000XLS, is up to 16"(41 cm) with 3000XLS, and is up to 21"(53 cm) with 4000XLS
- Operator length for 2000XLS: with arm fully retracted is 33.75" (85.2 cm), mounting point to mounting point
- Operation, diagnostic, and safety alarms
- Inherent obstruction sensing so the operator meets UL without external sensing devices
- Soft start/soft stop—for long mechanical life expectancy
- Auto close adjustable 3–120 seconds delay

Series Specification

Model	Type	Volts	Max. Gate Length	Max Gate Weight	Gate Speed
PRO-SW4000XLS	Single	12 V DC	20'	1000 lbs	18-20 sec
PRO-SW4200XLS	Second Arm	12 V DC	20'	1000 lbs	18-20 sec
PRO-SW3000XLS	Single	12 V DC	16'	650 lbs.	15-18 sec.
PRO-SW3200XLS	Second Arm	12 V DC	16'	650 lbs.	15-18 sec.
PRO-SW2000XLS	Single	12 V DC	16'	500 lbs.	15-20 sec
PRO-SW2002XLS	Dual	12 V DC	16'	500 lbs.	15-20 sec



All Models Listed; UL325 Compliant



Supporters and Proud Members of



CAUTION

- Automatic gates not for pedestrians
- Automatic gate operators designed for vehicular traffic only; operators are powerful and can cause serious injury or death; DIRECT ALL PEDESTRIAN TRAFFIC TO SEPARATE PEDESTRIAN GATE



Linear® Garage Door Operators, Gate Operators, Access Controls and Radio Controls

Backed by 60 years of pioneering experience in wireless technology, garage door and gate operator manufacturing, and access control systems, the full breadth of the Linear® brand is a leading source for the garage door, gate, and access industries.

linear-solutions.com



Niceforyou.com

©2023 Nice North America LLC. Linear is a registered trademark of Nice North America LLC. All rights reserved. All other products or name brands are trademark of their respective holders.